


## ON-SLAB SINGLE GANG

The Minnich Single Gang On-Slab features on-slab drilling solutions for almost any project. The single drill series can drill in horizontal, vertical, 35° stitch positions, and is also capable of skew drilling for maximum versatility. All models feature steering to enhance operator accuracy and control and an automatic shut-off feature that extends drill life. They can also be equipped with a dust collection system to minimize dust and debris on the job site.

## FEATURES

- Horizontal, Vertical, and 35° Stitch
- Urethane Filled Tires
- Adjustable Drill Height, Depth, and Centers
- Low Oil Level Indicator

## OPTIONS

- 3.25” Drill Chucks
- Dust Collection
- On-Grade Kit
- Non-Steering Model

## SPECIFICATIONS

| | 48 | 36 | 30 | 24 |
|---|---|---|---|---|
| Drill Steel Shank Size | .875” x 4.25” | .875” x 4.25” | .875” x 3.25” | .875” x 3.25” |
| Drill Steel Length | 24” | 12” | 12” | 9” |
| Drill Bit Diameter | .625” - 2.50” | .625” - 2.50” | .625” - 1.625” | .625” - 1.00” |
| Maximum Hole Depth | 18” | 10” | 10” | 7” |
| Minimum Cutout Width | 48” | 36” | 30” | 24” |
| Distance from Top of Slab | 2.5” - 12.75” | 3” - 12” | 3” - 12” | 3” - 12” |
| Required SCFM | 92.2 | 92.2 | 90 | 36 |
| Required PSIG | 120 | 120 | 90 | 90 |
| Weight | 700 LBS | 665 LBS | 630 LBS | 605 LBS |